

## Client SSD

HG6 Series ( Non-SED model )

		2.5-inch Case ( 9.5 mm Height )	2.5-inch Case ( 7.0 mm Height )	mSATA Module	M.2 2280-D2 ( Double-sided )	M.2 2280-S2 ( Single-sided )
<b>Basic Specifications</b>						
Model Number	512 GB	THNSNJ512GBSU	THNSNJ512GCSU	THNSNJ512GACU	THNSNJ512GDNU	-
	256 GB	THNSNJ256GBSU	THNSNJ256GCSU	THNSNJ256GMCU	THNSNJ256G8NU	THNSNJ256GVNU
	128 GB	THNSNJ128GBSU	THNSNJ128GCSU	THNSNJ128GMCU	THNSNJ128G8NU	THNSNJ128GVNU
	60 GB	THNSNJ060GBSU	THNSNJ060GCSU	THNSNJ060GMCU	THNSNJ060G8NU	-
Connector Type		Standard SATA	Standard SATA	mSATA	M.2 B-M	
Interface		ACS-2, SATA revision 3.1				
Interface Speed		6.0 Gbit/s , 3.0 Gbit/s , 1.5 Gbit/s				
Memory Type		MLC				
Sequential Read		Up to 534 MB/s { 510 MiB/s }				
Sequential Write		Up to 482 MB/s { 460 MiB/s }				
<b>Reliability</b>						
MTTF		1,500,000 hours				
<b>Power Requirements</b>						
Supply Voltage		5.0 V ±5 %		3.3 V ±5 %		
Power Consumption ( Active )		3.3 W Typ.		3.2 W Typ.		2.5 W Typ.
Power Consumption ( Idle )		125 mW Typ.		65 mW Typ.		
<b>Dimensions</b>						
Height		9.5 mm	7.0 mm	3.95 mm	3.58 mm	2.23 mm
Width		69.85 mm		30.0 mm	22.0 mm	
Length		100.0 mm		50.95 mm	80.0 mm	
Weight		51 to 55 g Typ.	49 to 53 g Typ.	7.3 to 7.7 g Typ.	7.0 to 9.3 g Typ.	6.4 to 6.6 g Typ.
<b>Environmental</b>						
Temperature ( Operating )		0 to 70 °C ( Case Temperature )		0 to 80 °C ( Components Temperature )		
Temperature ( Non-operating )		-40 to 85 °C				
Vibration ( Operating / Non-operating )		196 m/s <sup>2</sup> { 20 G } ( Peak, 10 to 2,000 Hz )				
Shock ( Operating / Non-operating )		14.7 km/s <sup>2</sup> { 1500 G } ( 0.5 ms )				
More Features		<ul style="list-style-type: none"> <li>• Translation mode which enables any drive configuration</li> <li>• Hot plug/OS-Aware removal</li> <li>• Toshiba's proprietary error-correction technology, QSBC support</li> <li>• Read only mode supported for emergency</li> </ul>				

- ▶ For additional information, please refer to HG6 Series Product Brief.
- ▶ Product image may represent a design model.
- ▶ Definition of capacity: Toshiba defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2<sup>30</sup> = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.
- ▶ A kibibyte (KiB) means 2<sup>10</sup>, or 1,024 bytes, a mebibyte (MiB) means 2<sup>20</sup>, or 1,048,576 bytes, and a gibibyte (GiB) means 2<sup>30</sup>, or 1,073,741,824 bytes.
- ▶ MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.
- ▶ Read and write speed may vary depending on the host device, read and write conditions, and file size.
- ▶ "2.5-inch" and "3.5-inch" mean the form factor of HDDs or SSDs. They do not indicate drive's physical size.
- ▶ QSBC: Quadruple Swing-By Code Technology