

SSD

> PX04SVB SERIES
ENTERPRISE VALUE ENDURANCE SSD



> KEY FEATURES

- Up to 3.84 TB Storage Capacity
- 270K IOPS random read
- 2.5-Inch Form-Factor, 15mm Z-Height
- 3 DWPD (Drive Writes Per Day) with 100% Random Workload
- Dual-Port 12.0 Gbit/s SAS Interface
- Improved Read/Write Bandwidth and Random IOPS
- Full Power-Loss-Protection and End-to- End Data Protection including T10 DIF
- Pin-3 Power Disable Support
- Self-Encrypting Option

> APPLICATIONS

- Media Streaming
- Data Warehousing
- Web Servers

> MAIN SPECIFICATIONS

Model Number		PX04SVB384 PX04SVQ384	PX04SVB192 PX04SVQ192	PX04SVB096 PX04SVQ096	PX04SVB048 PX04SVQ048
Interface		SAS-3.0 (12.0 Gbit/s, 6.0 Gbit/s, 3.0 Gbit/s, 1.5 Gbit/s)			
Formatted Capacity		3.84 TB	1.92 TB	960 GB	480 GB
Performance	Interface Speed	12.0 Gbit/s Max.			
	Memory Type	MLC			
	Sustained 64KiB Sequential Read	1,500 MiB/s	1,900 MiB/s		
	Sustained 64KiB Sequential Write	750 MiB/s	850 MiB/s		
	Sustained 4KiB Random Read	270K IOPS			
	Sustained 4KiB Random Write	55K IOPS	60K IOPS		
Supply Voltage	Allowable Voltage	5 V ± 7% 12 V ± 7%			
Power Consumption		3.2 W Typ.			

> RELIABILITY

Model Number	PX04SVBxxx PX04SVQxxx
MTTF	2,000,000 hours
DWPD	3
Warranty	5 years

> MECHANICAL SPECIFICATIONS

Model Number	PX04SVBxxx PX04SVQxxx
Height	15.0 mm + 0, -0.5 mm
Width	69.85 ± 0.25 mm
Length	100.45 mm Max.
Weight	150 g Max.

> ENVIRONMENTAL LIMITS

Item	PX04SVBxxx PX04SVQxxx
Temperature	Operating 0 °C to 55 °C
Humidity	Operating 5 % to 95 % R.H. (No condensation)
Vibration	Operating 21.27 m/s ² { 2.17 Grms } (5 to 800 Hz)
Shock	Operating 9,800 m/s ² { 1,000 G } (0.5 ms duration)

Definition of capacity: Toshiba defines a megabyte (MB) as 1,000,000 bytes, a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2³⁰ = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary.

A kibibyte (KiB) means 2¹⁰, or 1,024 bytes, a mebibyte (MiB) means 2²⁰, or 1,048,576 bytes, and a gibibyte (GiB) means 2³⁰, or 1,073,471,824 bytes.

MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF.

DWPD: Drive Write Per Day. One full drive write per day means the drive can be written and re-written to full capacity once a day every day for five years, the stated product warranty period. Actual results may vary due to system configuration, usage and other factors.

Read and write speed may vary depending on the host device, read and write conditions, and file size.

IOPS: Input Output Per Second (or the number of I/O operations per second)

PLP (Power Loss Protection): PLP supports to record data in buffer memory to NAND flash memory, utilizing back up power of solid capacitor in case of sudden supply shut down.